

MT2216

Notes: The test condition of temperature is motor surface temperature in 100% throttle while the motor run 10 min.

MT2216

APPLICATION FOR ALL PROPS

BEST CHOICE FOR UPGRADING YOUR F450 F550 ORIGINAL MOTOR

-----PROMOTING EXTRA PAYLOAD

----- PROTECT YOUR FLIGHT SAFETY.



完美提升你的载重空间，为您的安全飞行保驾护航


Efficient

Stable

Durable



EZO bearing to improve the life of the motor, which is imported with original packaging (not used bearing, low level EZO bearing, Fake bearing). Office test indicate which can complete the flight time is 60-80 hours. we stronger suggest to change the bearing after your flight getting 60 hours to surance you safe flight whether the bearing getting bad or not because the bearing is consumer parts of the motor.



The tight and orderly winding is professional by hand, Compared with the loose winding motor, the instant current would be lower 15% , and the load current would be lower 5-10% , have higher efficiency and more torque

T-MOTOR standard packing
PS: 3pcs M2*8 bolts are
used for prop adapter
installation

4pcs M3*6 bolts are used
for mounting plate
installation.

Be sure not to use these
bolts for motor installation.
As the thickness of motor
bracket is different on the
market, the standard
packing is without motor
mounting screws connecting
the frame and motor.



The standard packing is
included M5 CW prop
adapter (item No. PA001)
It is suitable for APC and
other M5 props. If you
choose M5 CCW prop
adapter (item No. PA002)
instead, it will be self lock

T-MOTOR standard packing
PS: 3pcs M2*8 bolts are
used for prop adapter
installation

4pcs M3*6 bolts are used
for mounting plate
installation.

Be sure not to use these
bolts for motor installation.
As the thickness of motor
bracket is different on the
market, the standard
packing is without motor
mounting screws connecting
the frame and motor.



The standard packing is
included M5 CW prop
adapter (item No. PA001)
It is suitable for APC and
other M5 props. If you
choose M5 CCW prop
adapter (item No. PA002)
instead, it will be self lock

for more safety.



If you choose M5 CW short prop adapter (item No. PA003) and M5 CCW short prop adapter (item No. PA004), T-MOTOR CF props can be installed on the motor. It will be self lock for more safety. The combination of MT2216 V2.0 and T-MOTOR CF prop will get much better flight

If you choose M6 CW short prop adapter (item No. PA029) and M6 CCW short prop adapter (item No. PA030), The props for DJI Phantom V1 & V2 can be installed on the motor directly.



Perfect packing

T-MOTOR
THE SAFEST PROPULSION SYSTEM



E-MOTOR
HIGH PERFORMANCE BRUSHLESS MOTORS





7-MOTOR
HIGH PERFORMANCE BRUSHLESS MOTORS



T-MOTOR
HIGH PERFORMANCE BRUSHLESS MOTORS



Z-MOTOR
HIGH PERFORMANCE BRUSHLESS MOTORS

