


Run

Instruction Diagram



- Front MIC
- 2 Camera Status Light (LED1)
- Power/Shutter button
 - Battery Status Light

Ö (IP) 0 6 WiFi/Mode Button

- 6 WiFi/Charging Status Light (LED2)
 - Back MIC Micro USB

Charging

Micro-USB supports DC 5-15V power supply. A DC 5V1~2A charger is recommended. The charging status light (red) will turn on during charging and turn off when charging is complete. It takes about 2 hours to get fully charged. **Battery Status**

		• •	•	Blink
>66% <66% >33% <10%	>66%	<66%	>33%	<10%

asic Camera Operation	
Powering On/Off	• Long press the Power/Shutter button
WiFi On/Off	Short press the WiFi/Mode button If the WiFi/Charging Status Light (LED2) blinks blue, it means it is ready to be connected and it will stop blinking and become constantly on after being connected. Default SSID: RC3S ******* (* for letters or numbers) Default WiFi password: 1234567890
Mode Switching	After powering on, long press the WiFi/Mode button to cycle among the three modes: Video/Photo/OSD setting.
Video Mode	Camera Status Light (LED1): Red - Press the Power/Shutter button to start/stop recording.
Photo Mode	Camera Status Light (LED1): Green • Press the Power/Shutter button to capture photos.
OSD Setting Mode	Camera Status Light (LED1): Orange - Press the Power/Shutter button to browse. - Press the WiFi/Mode button to select. - Long press the WiFi/Mode button to exit the current menu.
Forced Shutdown	Simultaneously press the Power/Shutter button and WiFi/Mode button.
Reset	In standby mode, press the WiFi/Mode button three times in rapid succession. The camera status light (orange) blinks twice. The camera completes its resetting and then automatically shuts down.

Use brand name memory cards (sold separately) that meet these requirements:

microSD card

· microSD, microSDHC, or m · Class 10/UHS-I/UHS-II/UHS-III

Insert the microSD card as indicated by the icon next to the card slot

Capacity up to 64GB



....©

Connection to computer

ø



App



our website: https://runcam.com/download/runcam39

- Firmware upgrade
- Firmware Upgrade Status (orange lights blink) Ensure that the RunCam 3S battery is more than 50% before the upgrade. **Method 1 (recommended):**Connect your camera to your smartphone/tablet. If an update is available, the App provides instructions for installing it.

Method 2:

OSD Settings (TV-OUT)

Manually copy the firmware file (RC3S.BRN) onto the microSD card. Follow the instruction on https://runcam.com/download/runcam3s. To get the latest features and best performance from your RunCam 3S, make sure you are using the most current camera software. You can update your firmware with the RunCam App or at https://runcam.com/download/runcam3s.

WiFi/Mode button Support DC5-17V external power



Parameter				
Video Resolution	1080p@60fps/1080p@50fps/1080p@30fps/ 720p@60fps			
Video File Format	MOV			
Image Resolution	2MP			
AV Output Format	NTSC/PAL			
Communication Interface	Micro USB			
microSD card supported	64G max			

Video File Format	MOV
Image Resolution	2MP
AV Output Format	NTSC/PAL
Communication Interface	Micro USB
microSD card supported	64G max
Battery Capacity	850mAh
USB Power Input	DC 5-15V

620mA @5V 40*38*37mm

69g (with battery)

Dimension Net Weight

Check Complete User Manual

Please visit: https://runcam.com/download/runcam3s

Technical Support

Please visit: https://support.runcam.com